

EVERLAST II™

THE NEXT GENERATION OF CONFIDENCE
FOR RESIDENTIAL ROOFING



EVERLAST II™

Attractive Design

The symmetrical pattern of Everlast II™ creates an attractive board and batten look, which is a popular choice. The crisp, clean appearance, along with the variety of color options available, make it the perfect roof for residential buildings. A full line of trims and accessories are available to complete your building project. The panels, which interlock to create the attractive look, also provide for the weathertight seal. They have a deep antisiphon groove, which protects against leakage.

Superior Strength


Everlast II™ is 38" wide and provides 36" of coverage. The major ribs are 9" apart and approximately 3/4" high with two minor ribs in between that are a full 3/16" high. A stiffener is added to all the major ribs, which, along with the superior thickness of the steel, makes this panel extremely strong. This not only adds considerable durability to your building, but also prevents rippling during the construction process.



SERIES	OMNI PREMIUM OPTION	LYNX	GALFAN GF90
GAUGE	27 Gauge	28 Gauge	29 Gauge
SUBSTRATE / FINISH	AZM125® WITH ACTIVATE® TECHNOLOGY COLORBOND®	AZM110® WITH ACTIVATE® TECHNOLOGY COLORBOND® CERAM-A-STAR® 1050 MATTE	GF90 Equivalent to G180 CERAM-A-STAR® 1050 MATTE
FILM INTEGRITY	50 YEARS	40 YEARS	40 YEARS
FADE OR CHALK	35 YEARS	35 YEARS	35 YEARS
RED RUST	15 YEARS	10 YEARS	10 YEARS
PERFORMANCE	25 YEARS	25 YEARS	25 YEARS

UL Ratings

- UL Construction No#560 UPLIFT TEST
- UL 2218 Class 4 IMPACT RESISTANCE
- UL 790 Class A FIRE RESISTANCE



MID-ATLANTIC
10 Enterprise Court
Lebanon, PA 17042

CENTRAL
161 Grand Valley Ave.
Orwell, OH 44076

MIDWEST
7180 N 050 E
Howe, IN 46746

NEW ENGLAND
24 JR Mains Drive
Bridgton, ME 04009